



CRUSHPROOF® TUBING

EXHAUST HOSES

Crushproof® Tubing Company has been leading the exhaust hose industry through innovative design and on-going development since 1949. We have the most complete and affordable line of exhaust service products available.

- Can be crushed by a vehicle and will return to original shape (non-wire versions).
- Use for temperatures up to 600°F with proper system in place.
- Best value. Costs far less than alternatives and easier to install.
- Our threaded adapters can be quickly screwed onto or into the tubing.
- Join hoses together without the need of a separate splice (FlareLok only)

FLARELOK® HOSE

| | |
|---------------|----------------------|
| FLT200 | 2" ID X 11' LENGTH |
| FLT250 | 2.5" ID X 11' LENGTH |
| FLT300 | 3" ID X 11' LENGTH |
| FLT400 | 4" ID X 11' LENGTH |



FLARELOK®

ACT HOSE

| | |
|------------------|------------------------------|
| ACT400 | 4" ID X 11' LENGTH |
| <i>ACT400W11</i> | <i>4" ID X 11' WITH WIRE</i> |
| ACT500 | 5" ID X 11' LENGTH |
| <i>ACT500W11</i> | <i>5" ID X 11' WITH WIRE</i> |
| ACT600 | 6" ID X 11' LENGTH |
| <i>ACT600W11</i> | <i>6" ID X 11' WITH WIRE</i> |



ACT
(shown with wire)

*add suffix W11 for 11' of wire or W30 for 30" of wire

20 FOOT OPTIONS

| | |
|--------------|--------------------|
| 40-20 | 4" ID X 20' LENGTH |
| 50-20 | 5" ID X 20' LENGTH |

*standard Crushproof accessories will fit this style if they screw inside the hose.



ACT 20'



Phone: 800-654-6858 or 419-293-2111
Fax: 419-293-2609
Email: contact49@crushproof.com
Location: 100 North Street McComb, Ohio 45858

crushproof.com

OR

SCAN THE QR CODE
FOR DIRECT ACCESS
TO OUR WEBSITE

